

# Datasheet Conveyor Belt



## NITTA CORPORATION OF HOLLAND

Berenkoog 25  
1822 BH Alkmaar  
The Netherlands

T: +31 (0)72 562 22 34  
F: +31 (0)72 561 32 38

E: sales@nitta.nl  
www.nittacorporation.com

- **NITTA BELT TYPE:**  
**2 N 371**
- **Nitta Japan code:**



**Construction:** 2 plies polyester, non-rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
<b>Material:</b>	PVC	PVC	PVC	
<b>Thickness:</b>	0,7		0,55	<b>mm (approx.)</b>
<b>Colour:</b>	Blue	Blue	Blue	
<b>Hardness:</b>	65 Shore A		90 Shore A	
<b>Profile:</b>	-		SQPR	

<b>Total thickness:</b>	3,2	<b>mm (approx.)</b>
<b>Weight:</b>	3,9	<b>kg/m<sup>2</sup> (approx.)</b>
<b>Max. width:</b>	3000	<b>mm</b>
<b>Belt support:</b>	Sliderbed (Rollers), Flat/trough	

<b>Rating at 1% elongation:</b>	12	<b>N/mm</b>
<b>Advised pretension:</b>	4 - 7	<b>N/mm</b>
<b>Maximum allowable tension:</b>	22	<b>N/mm</b>
<b>Temperature range:</b>	-10 to +90	<b>°C</b>

<b>Minimum pulley diameters:</b>		
<b>Flexing:</b>	50	<b>mm</b>
<b>Backflexing:</b>	80	<b>mm</b>

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:**

- Oil and grease resistant
- Conveyor belt in bakeries
- Conveying of meat, fish and poultry products
- Blue colour makes possible product contamination visible
- Conveyor belt for the food industry

Date of issue 07-07-2014-2

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com